

BRYAN BOILERS

AB-WEB-LX
DATE: 07/15/14

Originators of the "Flexible Water Tube" design

**WEBSTER LOW NO_x BASE BURNER DATA
"AB" SERIES BOILERS
SUB 30 PPM - GAS / REDUCED NO_x OIL**

BOILER MODEL	INPUT		BASE BURNER MODEL (1)	COMBUSTION CONTROL MODEL/SCANNER (2)		IGNITION MEANS (3)	MOTOR DATA (4)	FIRING SYSTEM GAS	GAS TRAIN DATA			OIL DATA			
	MBH	GPH		GAS	GAS/OIL				GAS & G/O	HP	TRAIN SIZE NPT	STANDARD PRESS IN. W.C./PSI		PUMP LOC (5)	SUC. CAP (GPH)
												MIN	MAX		
AB 90	Not Available														
AB 120	1200	8.6	JBX1 - **	RM7897C/UV	RM7897C/UV	GP	1/2	Modulation	1-1/2"	8.0"	1#	BM	45		
AB 150	1500	10.7	JBX1 - **	RM7897C/UV	RM7897C/UV	GP	3/4	Modulation	2"	8.0"	1#	BM	45		
AB 200	2000	14.3	JBX2 - **	RM7897C/UV	RM7897C/UV	GP	3/4	Modulation	2"	12.0"	1#	BM	70		
AB 250	2500	17.8	JBX2 - **	RM7897C/UV	RM7897C/UV	GP	1	Modulation	2"	14.0"	1#	BM	70		
AB 300	3000	21.4	JBX2 - **	RM7840L/UV	RM7840L/UV	GP	2	Modulation	2"	15.0"	1#	BM	70		

STANDARD GAS TRAIN COMPONENTS

COMPONENT	AB 90	AB 120 TO AB 250	AB 300
Manual Shutoff Valve (point of field connection)	STD.	STD.	STD.
Gas Pressure Regulator	STD.	STD.	STD.
Main Oper. Gas Valve - Diaphragm type	STD.	STD.	STD.
Main Oper. Gas Valve - Motorized type	OPT.	STD.	STD.
Auxiliary Oper. Gas Valve - Solenoid type	STD.	STD.	STD.
Low Gas Pressure Switch	OPT.	OPT.	STD.
High Gas Pressure Switch	OPT.	OPT.	STD.
Manual Checking Shutoff Gas Valve	STD.	STD.	STD.
STANDARD OIL COMPONENTS			
Dual Shutoff Valves	STD.	STD.	STD.

- ABBREVIATIONS:
- (1)** Insert: "G" - Gas, "C" - Gas/Oil, (4) Motor Voltage: 60 Hz - Motor RPM: 3450 RPM
 - (2) Combustion Control: 1/3 HP & 1/2 HP = 120/1 Ph
 - Model - RM7897C, RM7840L 3/4 HP & 1 HP = 230/1 Ph
 - Scanner : "UV" - Ultra Violet 1 1/2 HP & Larger = 208-240-480/3 Ph (please specify)
 - (3) Ignition means: (5) Oil Pump Location:
 - "GP" - Gas Pilot "BM" - Burner Mounted

- NOTES >>>**
- Burner capacities listed for elevations up to 2,000 ft. For higher elevations, consult local Bryan Boilers sales office.
 - Oil ratings based on No. 2 fuel with heating value of 140,000 Btu per gallon.
 - Gas rating based on natural gas with heating value of 1000 Btu per cubic foot and specific gravity of .60. Gas burners for other gases are available, consult local Bryan Boilers sales office.



783 N. Chili Ave., Peru, Indiana 46970
Telephone: (765) 473-6651
Fax: (765) 473-3074
E-Mail: inquiry@bryansteam.com
Internet: www.bryanboilers.com