BRYAN BOILERS

Originators of the "Flexible Water Tube"

WEBSTER ENGINEERING BASE BURNER DATA "DR" SERIES BOILERS NATURAL GAS / No. 2 OIL

		цт	BASE	COMBUSTION CONTROL				MOTOR		GAS TRAIN DATA			OIL DATA	
BOILER	ILER		BURNER	(2) MODEL/SCANNER		(3)		(4)	FIRING SYSTEM	TRAIN	STANDARD PRESS		PUMP	SUC.
MODEL	(MBH)	СРН	(1)	GAS &		GAS		ЦВ	GAS		IN. W.C.		LOC	CAP
	(тыры)	GFH		GAS / OIL	OIL	G/O		пг		INP I	MIN	MAX	(5)	(GPH)
DR250	250	1.8	NOT AVAILABLE											
DR350	350	2.5												
DR450	450	3.2	JB1-*	RM7897C/UV	R7284A/CC	GP	DS	1/3	ON-OFF	1"	7.0"	14.0"	BM	45
DR650	650	4.6	JB1-*	RM7897C/UV	R7284A/CC	GP	DS	1/3	ON-OFF	1"	7.0"	14.0"	BM	45
DR850	850	6.1	JB1-*	RM7897C/UV	R7284A/CC	GP	DS	1/3	ON-OFF	1-1/4"	7.0"	14.0"	BM	45

STANDARD GAS TRAIN COMPONENTS								
COMPONENT	BOILER MODEL							
COMPONENT	DR450 to DR850							
Manual Shutoff Valve (point of field conn.)	STD.							
Gas Pressure Regulator	STD.							
Main Operating Gas Valve	STD.							
Auxiliary Operating Gas Valve	STD.							
Manual Checking Shutoff Gas Valve	STD.							
STANDARD OIL COMPONENTS								
Dual Shutoff Valves	STD.							

ABBREVIATIONS:

(1)Insert: "G" = Gas "C" = Gas / Oil "O" = Oil
(2) Combustion Control: Model - RM7897C Model - RM7284A Scanner - "UV" - Ultra Violet "CC" - Cad Cell (3) Ignition means:
"GP" - Gas Pilot
"DS" - Direct Spark
(4) Motor Voltage:
1/3 HP = 120/1 Ph / 60 Hz
Motor RPM: 3450 RPM
(5) Oil Pump Location:
"BM" - Burner Mounted

NOTES: >>>

- 1. Burner capacities listed for elevations up to 2,000 ft. For higher elevations, consult local Bryan Boilers sales office.
 - 2. Oil ratings based on No. 2 fuel with heating value of 140,000 Btu per gallon.
 - 3. Gas rating based on natural gas with heating value of 1000 Btu per cubic foot and specific gravity of .60. Gas burners for other gases are available, consult local Bryan Boilers sales office.



783 N. Chili Ave., Peru, Indiana 46970Telephone:(765) 473-6651Fax:(765) 473-3074E-Mail:inquiry@bryansteam.comInternet:www.bryanboilers.com

